



Vehicle model	DAILY 3.0 A50C17 / A50C17P / A65C17 / A65C17P 70C17		DAILY 3.0 A50C17 / A50C17P / A65C17 / A65C17P 70C17		DAILY 3.0 A50C17 / A50C17P / A65C17 / A65C17P 70C17		DAILY 3.0 A50C17 / A50C17P / A65C17 / A65C17P 70C17		DAILY 3.0			
Year	(01/2012)		(01/2012)		(01/2012)		(01/2012)		(2004>)			
Engine Type	F1CE3481K (Euro 5) F1CFL411H*C (Euro 5b+) F1CFL411F*A (Euro 6)		F1CE3481K (Euro 5) F1CFL411H*C (Euro 5b+) F1CFL411F*A (Euro 6)		F1CE3481K (Euro 5) F1CFL411H*C (Euro 5b+) F1CFL411F*A (Euro 6)		F1CE3481K (Euro 5) F1CFL411H*C (Euro 5b+) F1CFL411F*A (Euro 6)		F1C 3.0 (Euro 3-4)			
CV(kW) @ rpm	170 (125) @ 3.500 180 (132) @ 3.500		170 (125) @ 3.500 180 (132) @ 3.500		170 (125) @ 3.500 180 (132) @ 3.500		170 (125) @ 3.500 180 (132) @ 3.500		170 (125) @ 3.500			
N. of cylinders/cm3	4 / 2.998		4 / 2.998		4 / 2.998		4 / 2.998		4 / 2.998			
Volts	12		12		12		12		12			
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Only Vehicles without A/C			
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge		
Compressors type	TM 16 UP-UPF 170		TM 16 UP-UPF 170		TM 21 / QP21		TM 21 / QP21		TM 21			
Comments	<ul style="list-style-type: none"> - "E"=TM-UNICLA; - UNICLA: Clutch drive plate Ø120 not suitable. - Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 		<ul style="list-style-type: none"> - Can be fit in right hand drive vehicles - THE ORIGINAL ACCESSORIES BELT IS KEPT - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 		<ul style="list-style-type: none"> - Can be fit in right hand drive vehicles - THE ORIGINAL ACCESSORIES BELT IS KEPT - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 		<ul style="list-style-type: none"> - Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 		<ul style="list-style-type: none"> - Only for vehicles with original 504180619. - Can be fit in right hand drive vehicles. 			
Clutch type	Without clutch pulley	With clutch pulley	Without clutch pulley	Without clutch pulley	Without clutch pulley	Without clutch pulley	Without clutch pulley	With clutch pulley	Without clutch pulley			
	Poly-V 8K Ø119 4.560 rpm	Poly-V 8K Ø119 4.560 rpm	Poly-V 8K Ø119 4.560 rpm	Poly-V 8K Ø137 3.960 rpm	Poly-V 8K Ø137 3.960 rpm	Poly-V 8K Ø137 3.960 rpm	Poly-V 8K Ø137 3.960 rpm	Poly-V 8K Ø137 3.960 rpm	Poly-V 8K Ø137 4.087 rpm			
Kit No.	KB15018069		KB15018069E		KB17118085		KB17118086		KB15028070		KB15028070E	KB10018012
Last update	2019-06-07		2018-08-10		2018-08-10		2016-11-30		2012-06-22			

Vehicle model	EuroCargo	EuroMidi CC100E22FP	EuroMidi CC100E22FP	EuroMidi CC150E25FP		
Year	(2014>)	(2010>)	(2010>)	(2010>)		
Engine Type	F4AFE611A°C (Euro 6) F4AFE611E°C (Euro 6) F4AFE611C°C (Euro 6) F4AFE611D°C (Euro 6)	F4AE3681B (Euro 4-5) F4AFE611A°C (Euro 6)	F4AE3681B (Euro 4-5) F4AFE611A°C (Euro 6)	F4AE3681D (Euro 4-5) F4AFE611E°C (Euro 6)		
CV(kW) @ rpm	220 (162) @ 2.500 250 (184) @ 2.500 280 (206) @ 2.500 320 (235) @ 2.500	217 (159) @ 2.700 220 (162) @ 2.700	217 (159) @ 2.700 220 (162) @ 2.700	251 (184) @ 2.700		
N. of cylinders/cm3	6 / 6.700	6 / 5.880 6 / 6.728	6 / 5.880 6 / 6.728	6 / 5.880 6 / 6.728		
Volts	24	24	24	24		
Air Conditioning	Vehicles with or without A/C	Vehicles with or without A/C	Vehicles with or without A/C	Vehicles with or without A/C		
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge
						
Compressors type	TM 31	TM 31	TM 31	TM 31		
Comments	- Can't be fit in right hand drive vehicles. - No suitable for 220HP engine with automatic gear box.	- Compressor fittings not supplied in the kit	- Compressor fittings not supplied in the kit - Suitable for front box AC	- Compressor fittings not supplied in the kit		
Clutch type	Without clutch pulley	Without clutch pulley	Without clutch pulley	Without clutch pulley		
	2B Ø158 2.975 rpm	2B Ø158 3.400 rpm	2B Ø158 3.400 rpm	2B Ø158 3.400 rpm		
Kit No.	KB13038048	KB15068075	KB16048081	KB11018024		
Last update	2014-03-28	2015-06-17	2016-04-29	2015-06-17		